THE 1997 ASIAN PACIFIC MATHEMATICAL OLYMPIAD

Time allowed: 4 hours
NO calculators are to be used.
Each question is worth seven points.

Question 1

Given

$$S = 1 + \frac{1}{1+\frac{1}{3}} + \frac{1}{1+\frac{1}{3}+\frac{1}{6}} + \cdots + \frac{1}{1+\frac{1}{3}+\frac{1}{6}+\cdots+\frac{1}{1993006}} ,$$

where the denominators contain partial sums of the sequence of reciprocals of triangular numbers (i.e. $k = n(n+1)/2$ for $n = 1, 2, \ldots, 1996$). Prove that $S > 1001$.

Question 2

Find an integer n, where $100 \leq n \leq 1997$, such that

$$\frac{2^n + 2}{n}$$

is also an integer.

Question 3

Let ABC be a triangle inscribed in a circle and let

$$l_a = \frac{m_a}{M_a} , \quad l_b = \frac{m_b}{M_b} , \quad l_c = \frac{m_c}{M_c} ,$$

where m_a, m_b, m_c are the lengths of the angle bisectors (internal to the triangle) and M_a, M_b, M_c are the lengths of the angle bisectors extended until they meet the circle. Prove that

$$\frac{l_a}{\sin^2 A} + \frac{l_b}{\sin^2 B} + \frac{l_c}{\sin^2 C} \geq 3,$$

and that equality holds iff ABC is an equilateral triangle.

Question 4

Triangle $A_1A_2A_3$ has a right angle at A_3. A sequence of points is now defined by the following iterative process, where n is a positive integer. From A_n $(n \geq 3)$, a perpendicular line is drawn to meet $A_{n-2}A_{n-1}$ at A_{n+1}.

(a) Prove that if this process is continued indefinitely, then one and only one point P is interior to every triangle $A_{n-2}A_{n-1}A_n$, $n \geq 3$.

(b) Let A_1 and A_3 be fixed points. By considering all possible locations of A_2 on the plane, find the locus of P.

Question 5

Suppose that n people A_1, A_2, $\ldots$, A_n, $(n \geq 3)$ are seated in a circle and that A_i has a_i

objects such that

$$a_1 + a_2 + \cdots + a_n = nN,$$

where N is a positive integer. In order that each person has the same number of objects, each person A_i is to give or to receive a certain number of objects to or from its two neighbours A_{i-1} and A_{i+1}. (Here A_{n+1} means A_1 and A_n means A_0.) How should this redistribution be performed so that the total number of objects transferred is minimum?